


CIC BIM Competition 2020 – Formula of Gravity

Location Plan 1:2000



About the New Development of the Student Hostel

Design Concept: What is the design rational for the Building Design?
Shear wall system will be chosen as boxes and partitions are required to separate the rooms in dormitory building, which will be suitable for inserting shall walls. As the floor-by floor repetitive planning is often used in student accommodation and residential building, vertically continuous shear wall design will be adopted in this project.

Building Form: How does the building form relates to the surrounding site context?
Buildings surrounding the site, such as schools and the YMCA centre, are low rise buildings, which then across the roads there are the high rise residential buildings. Considering environmental aspect and based on nearby structures, building is designed to enhance comfortability, service and to cater the nearby environment.

Spatial Arrangement: How is the Dormitory Areas, Common Areas and Sports Facility being arranged?
All dormitory areas are assigned on 3/F - 10/F, where include one common area per floor. The 2/F consist of plant room and gym house. The study and meeting area are located on 1/F, with half of the floor occupied by a sport center of two floor high from ground floor. Serval common area and parking area are included on the ground floor.

Connectivity: What is the vehicular and pedestrian connectivity, accessibility and evacuation considerations?
The public and residents can enter our building through the bridge from down the hill or the ground level roads. Vehicles can be enter our site through the roads on the ground floor level.

BIM Uses in Design, Collaboration, Engineering, Analysis and Optimisation: What is the defined BIM uses in carrying out design, collaboration, engineering, analysis and optimisation?
3D coordination, 4D scheduling are the important BIM uses throughout the project, it helps find out conflicts and we will give solutions to minimise possible logical or structural problems in the design.

BIM Collaboration approach: What is the approach and BIM tools for design collaboration?
The Wind loads simulation in AutoDesk Robot Structural Analysis is used to simulate a wind flow around the structure, and generate wind loads automatically. Dynamo is used to used for scripting, which helps to ensure our project is well coordinated. Naviswork is used to detect clash. Civil 3D is used to analysis the soil condition for making foundation choice. Fuzor is used to simulate the construction process and spot potential flaws of the project. Enscape is used to render our revit project. AutoCad is used for preliminary drawing which is further developed through Revit.


Quality of Design: How BIM improve the quality of design?
With the support of BIM tools, accurate calculations and estimations have been taken out, with lack of constructional problems, BIM enhances the quality of design in terms of sufficient geometry information, data managements etc.

Sustainability: How are the considerations of sustainability aspect and passive building design being achieved?
Curtain walls (3-10/F) and glass structure (G/F) are adapted to maximise natural sunlight while sky garden (2/F), green walls and solar panels (roof) minimise direct sunlight from reaching the structure. These approaches enhance the energy efficiency of the building. Besides, wind turbines and solar panels are installed on the rooftop, so that some of the energy consumed by the building can be supported by renewable energy.


MiC/ DfMA: How is Design for Modular Integrated Construction or Manufacturing and Assembly being involved in the design considerations?
There are type of 9 Mic units forming the student rooms, for modular unit with a width larger than 2.5 metres is required to make special traffic arrangement. Temporary storage location or special traffic arrangement needs to be made for transportation of modular units with width larger than 2.5 meters. Therefore, night transportation will be arranged so as to fulfil the transportation law.

Constructability: Any innovative approach introduced for construction?
Sky Garden, high ceiling lobby and reception, outdoor movie area



Summary: How BIM influences the design, engineering and design collaboration?
BIM facilitates the project efficiency, improves the accuracy of the details through real-time connection with teammates, robot simulation, loads analysis and calculation.




Conceptual Diagram: The concept of the building is a merge concepts of space, shape and comfortable living, which hence suits to the environment and provide practical uses.




Overall Bird Eye view: The building, which suits the environment with similar building height and accordingly to the ground conditions, will be built at a irregular shape which fulfills spatial requirement and services, such as sports ground, gym room, single room, visitor's romm etc.




Building Form and Space: The building design of this project to separate but also to provide suitable services for private living, which fulfills both building requirements, personal space and public space.



Quality: The use of BIM helps moderate development in stages of design, construct and imitation of the building design.
Autocad: provide platform to form suitable designs and plots.
Revit: supports the build up of structures, engineering, and building services elements.
Fuzor: shows present the possible look of the building with the adopted building method(MiC)



Solar panels & wind turbines on the roof floor




Sky Garden (3/F)



G/F & 1/F:
Lobby and Reception with curtain wall


Living floors (3-10/F)
Common area with curtain walls



Sustainability: Sky Garden are built on the roof of the stadium as leisure area for residents. Curtain walls are also adopted to maximize natural lighting and reduce electrical demand. Renewable energy devices are also installed.

CIC BIM Competition 2020 – Formula of Gravity

Site Layout Plan 1:1000




3D View showing the Height of each surrounded buildings




Perspective View: The reception and common area on the ground floor adopted a curtain wall design to maximize natural lighting and minimize the need of artificial lighting. Besides, in order to increase the sense of space, G/F and 1/F combined to create a high ceiling.

Section XX



Section YY




- Adjoining Condition**
1. Kwai Hop Street Playground
 2. TWGHs Chen Zao Men College
 3. Chinese YMCA of Hong Kong New Territories Centre
 4. The Methodist Lee Wai Lee College
 5. Daughters of Mary Help of Christians Siu Ming Catholic Secondary School
 6. Sak B. M. Kotewall Memorial School
 7. Salesians of Don Bosco Ng Siu Mui Secondary School
 8. Kwai Chung Estate Chun Kwai House
 9. S.K.H. Yan Lap Primary School
 10. Sheng Kung Hui Lam Woo Memorial Secondary School
 11. ELCHK Grace Lutheran Church
 12. Fung Yat Social Service Complex
 13. Kwai Hong Court East
 14. Kwai Shing East Estate Shing Fung House and Shing Hei House
 15. Basketball Court
 16. Kwai Hong Court Shing Fu House
 17. Kwai Shing East Comm. Complex

Computational Design:

The figure above shows that schools nearby are the major element which might be affected by the environmental impact caused by the construction activities.


Among the above, the most affected element is undoubtedly the surrounded schools that next to our site, and the estates nearby.




Ground Floor Plan 1:500



Typical Floor (3/F) Plan 1:500



Internal Perspective of student room 1:500



Overall Bird Eye view (Night View)

Figure 10 displays six screenshots of the HAP software interface, showing the results of wind pressure analysis for a building model. The results are presented for different wind directions:

- X+ Direction:** Result: 63.11 m/s
- X+ Y+ Direction:** Result: 151.95 m/s
- Y+ Direction:** Result: 202.07 m/s
- X- Direction:** Result: 89.13 m/s
- X- Y- Direction:** Result: 132.11 m/s
- Y- Direction:** Result: 63.57 m/s

1 Level FD Foundation Framing Plan
1:200


1 Level G Framing Plan
1:100

1 Level 1 Framing Plan
1:100

CIC BIM Competition 2020

BIM for Design Collaboration


CIC BIM Competition 2020 – Formula of Gravity



Project Summary


Location and Weather	
Project	Project Name
Address	
Calculation Time	Sunday, May 31, 2020 10:24 PM
Report Type	Standard
Latitude	42.21°
Longitude	-71.03°
Summer Dry Bulb	93 °F
Summer Wet Bulb	78 °F
Winter Dry Bulb	6 °F
Mean Daily Range	20 °F

Design Coordination: The sun path, shadow trace and the weather of the site can be stimulated by revit.



Internal Perspective of Typical Floor (3/F) 1:500

Perspective View: The plumbing and ventilation system are shown above. The plumbing system are independent in each room for easy installation of the MiC units. Central HVAC will supply fresh air to the common area of the building, while split AC will be used in student rooms.



Project Team Collaboration: BIM 360 is used to share files among group mates in real-time.

Hydronic System Air 12K											
System Information											
System Configuration		Report Air									
System Type		Report Air									
System Name		Hydronic System Air 12K									
System Location											
Load Pressure Loss Calculation by Section											
Section	Element	Flow	Size	Velocity	Velocity Pressure	Length	Loss Coefficient	Friction	Diameter	Total Pressure Loss	Section Pressure Loss
1	FRINGE	250.0 US	-	0.0 US	0.0 US	-	0.0075	-	-	0.79	0.79
2	air terminal	250.0 US	-	0.0 US	0.0 US	-	0.0075	-	-	0.79	1.474
3	Diff	250.0 US	-	0.0 US	0.0 US	800.0 mm	-	0.02106	400	0.79	0.79
4	FRINGE	250.0 US	-	0.0 US	0.0 US	-	0.0075	-	-	0.79	0.79
5	Diff	250.0 US	400000	0.0 US	0.0 US	1000 mm	-	0.02106	-	0.79	0.79
6	air terminal	250.0 US	-	0.0 US	0.0 US	-	0.0075	-	-	0.79	0.79
Total Path = 1.0 Total Path Length = 131.4 ft											
Global Information											
Section	Element	Flow	Size	Velocity	Velocity Pressure	Length	Friction Loss	Pressure Loss	Total Pressure Loss		
1	FRINGE	250.0 US	400	0.0 US	0.0 US	2.16	0.0075	0.0075	0.79	0.79	0.79
2	air terminal	250.0 US	400000	0.0 US	0.0 US	1.76	0.79	0.79	0.79	0.79	0.79
Fitting and Access Loss Coefficient Summary by Section											
Section	Element	Loss Method	Access Loss	Access Loss	Loss Coefficient	Pressure Loss	Total Pressure Loss				
1	U3E11	Coefficient Loss via Global Table	0.0	0.0	0.0075	0.79	0.79				
2	U3E11	Coefficient Loss via Global Table	0.0	0.0	0.0075	0.79	0.79				
3	U3E11	Coefficient Loss via Global Table	0.0	0.0	0.0	0.0	0.0				
4	U3E11	Coefficient Loss via Global Table	0.0	0.0	0.0	0.0	0.0				
5	U3E11	Coefficient Loss via Global Table	0.0	0.0	0.0	0.0	0.0				